

## Technical data

|                               |                   |
|-------------------------------|-------------------|
| Input voltage range           | 120 - 277 V AC    |
| Class                         | 1                 |
| IP                            | 65                |
| IK                            | 10                |
| Diffuser                      | Satin-finish PMMA |
| Bulb cover                    | No                |
| Source                        | Built-in LED      |
| Color temperature real output | 3000°K warm white |
| Real light output             | 1952 lm           |
| Total consupcion              | 26 W              |
| Energy class                  | A++ / A           |
| IRC                           | >80               |
| SDCM                          | -                 |
| Dimmable                      | No                |
| UGR                           | -                 |
| ULR                           | -                 |
| Photobiological Risk group    | No                |
| Fixing kit                    | Yes               |
| With sensor                   | No                |
| With IP55 socket              | No                |

[Download the installation manual](#)



## Materials and finishes

|          |           |
|----------|-----------|
| Material | aluminium |
|----------|-----------|

## Logistic data

|                      |                   |
|----------------------|-------------------|
| Product dimensions   | H.800 L.260 P.183 |
| Net weight           | 3.660 Kg          |
| Gross weight         | 5.310 Kg          |
| Package dimensions 1 | H.910 L.310 P.310 |

## Certifications and warranties

|      |     |
|------|-----|
| CE   | Yes |
| UL   | Yes |
| EAC  | Yes |
| RoHS | Yes |